

ORWAK COMPACT 3210

COMPACT

YOUR EFFICIENT PARTNER ORWAK COMPACT 3210

helps you take care of medium volumes of cardboard and plastic in no time! It is incredible fast and compacts your waste in just 13 seconds! Thanks to a small footprint, the 3210 fits where space is limited.



80 KG
BALE WEIGHT
CARDBOARD

Seconds



Orwak benefits

MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

MORE SPACE & ORDER

Our balers rapidly minimize the space the waste takes up, keeping aisles free and tidy.

LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO₂ emissions. Sorting at source yields a higher quality of waste material for recycling.



Why Orwak Compact?

- + Strong compaction on the spot! Requires little space, yet provides effective volume reduction
- + Easy-to-handle light weight bales
- + The best choice for small to medium size volumes of cardboard and plastic

ORWAK COMPACT 3210

Probably the fastest baler in the world

INCREDIBLY FAST

Compacts your waste in just 13 seconds!

EFFECTIVE COMPACTION

With a press force of 2.5 kg/sq. cm you achieve a volume reduction of up to 10:1

SMALL FOOTPRINT

The 3210 is a compact machine that takes up less than 1 sq. m floor space.

OPTIMAL BALE LOGISTICS

2 bales from model 3210 fit perfectly on one Euro pallet.



ORWAK COMPACT 3210 IS OPTIMIZED FOR:

PAPER

- + Cardboard
- + Shredded paper
- + Paper sacks

PLASTIC FOIL

- + Shrink film
- + Plastic bags

OTHER METALS

- + Steel straps

OTHER PLASTICS

- + Plastic straps

SWITCH BETWEEN LP AND HP

Compacting cardboard or plastic foil? A switch conveniently located on the side of the machine makes it simple to alter the setting from HP for cardboard to LP for plastic foil.

SILENT OPERATION CONTRIBUTES TO A BETTER WORKING ENVIRONMENT

Thanks to a silent type of hydraulics, the sound emission is low, which contributes to improving the working environment for the employees and is an important feature if the baler is installed close to customers.

BALE INDICATOR

A bale indicator alerts you when the machine has reached its capacity.


DIMENSIONS & SPECIFICATIONS

DIMENSIONS

A	B	C	D	E	F*
2150 mm	1081 mm	843 mm	1944 mm	706 mm	1795 mm

ENERGY CONSUMPTION

STANDBY MODE	MAXIMUM OPERATION ONE HOUR
2.7 W/H	626 W/H



Weight (machine) Total: 660 kg

*Transport height, must be ordered

TECHNICAL SPECIFICATIONS

LOADING APERTURE	CYCLE TIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER
Width: 800 mm Height: 500 mm	13 secs	HP 12 ton, 120 kN	Width: 800 mm Depth: 600 mm Height: 700 mm	Cardboard: Up to 80 kg Plastic: Up to 110 kg	62.4 db (A)	IP 55	3-phase 3x400 V, 50 Hz

We reserve the right to make changes to specifications without prior notice. Bale/bag/bin weights are dependent upon material type.