ORWAK FLEX 5010-E

FLEX

THE ORWAK FLEX 5010-E is a small but tough baler, that requires little space but offers effective compaction. The unit is sturdy, reliable and easy to operate.





Small footprint



Orwak benefits

MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

MORE SPACE & ORDER

Our balers rapidly minimizes the space the waste takes up, keeping aisles free and tidy.

LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO₂ emissions. Sorting at source yields a higher quality of waste material for recycling.





Why Orwak Flex?

- + Versatile compaction for many different application areas
- + Hygienic and safe compaction and disposal of mixed or hazardous waste
- + Special solutions for special needs



ORWAK FLEX 5010-E

Small but tough

ORWAK FLEX 5010-E IS OPTIMIZED FOR:

PAPER

- + Cardboard
- + Shredded
 - . . .
- PLASTIC FOIL
 + Shrink film
- + Plastic bags
- + Paper sacks

OTHER METALS

OTHER PLASTICS

+ Metal straps

+ Plastic straps

TOP LOADING

Feeding material into this top-loading baler is fast and convenient, and the compaction ratio is impressive thanks to high pressure on a small surface.

VERSATILE

The design means that the compactor is versatile and can be used for baling waste products such as cardboard, paper, plastic and even thin wood packaging.

COMPACT DESIGN


Thanks to its compact design, the baler fits where you need it to be and is easy to install in any location.



DIMENSIONS & SPECIFICATIONS

DIMENSIONS ORWAK FLEX 5010-E									
A	В	С	D	E					
7'1"	35''	43''	72"	51"					

ENERGY CONSUMPTION			
STANDBY MODE	MAXIMUM OPERATION ONE HOUR		
	660 W/H		



TECHNICAL SPECIFICATIONS											
LOADING APERTURE	CYCLETIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER				
Width: 20" Depth: 28"	36 secs	6,600 lbs.	Width: 28" Depth: 20" Height: 28"	Cardboard: Up to 110 lbs. Plastic: Up to 200 lbs.	70 db (A)	IP 55	Single phase 115 V, 60 Hz, 10 A				

We reserve the right to make changes to specifications without prior notice. Bale weights are dependent upon material type.



