# ORWAK COMPACT 3110

The ORWAK COMPACT 3110 is perfect for companies with small amounts of packaging waste. Thanks to the low height in combination with the small footprint, it fits where you need it to be! It is a small but effective baler and it gives a volume reduction up to 7:1.



# **ORWAK BENEFITS**



#### MORE PRODUCTIVE USE OF TIME

COMPAC

Less time spent on waste handling, more time for your core activities!

Complies to EN 16500 Safety standard

#### **MORE SPACE & ORDER**

Our balers rapidly minimize the space the waste takes up, keeping aisles free and tidy.

#### LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced  $CO_2$  emissions. Sorting at source yields a higher quality of waste material for recycling.

# WHY ORWAK COMPACT?

- Strong compaction on the spot! Requires little space, yet provides effective volume reduction
- Easy-to-handle light weight bales
- The best choice for small to medium size volumes of cardboard and plastic



# ORWAK COMPACT 3110

# Compact and versatile baler – fits where you need it!

## **SMALL FOOTPRINT**


The 3110 fits where you need it to be thanks to the compact design and small footprint.

#### AUTOSTART FOR EFFICIENT COMPACTION

An autostart function allows the baler to start compacting the material as soon as you close the door.

#### **BALE TROLLEY INCLUDED**

Model 3110 is always delivered with a bale trolley for effortless baling and smooth internal transportation of the bale.



В

866 mm

Adjustable bale size

DIMENSIONS & SPECIFICATIONS

### **A** 1990 mm

DIMENSIONS

ENERGY CONSUMTION	
STANDBY MODE	MAXIMUM OPERATION ONE HOUR
0.6 W/H	580 W/H

С

720 mm

#### **TECHNICAL SPECIFICATIONS**

LOADING APERTURE	CYCLE TIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	MACHINE WEIGHT	NOISE LEVEL	PROTECTION CLASS	OPERATING POWER
Width: 730 mm Height: 408 mm	33 secs	HP: 4 ton, 40 kN LP: 3 ton, 30 kN	Width: 700 mm Depth: 500 mm Height: 600 mm	Cardboard: Up to 50 kg Plastic: Up to 70 kg	252 kg	62.3 db (A)	IP 55	Single Phase 230 V, 50 Hz, 10 A

Е

694 mm

We reserve the right to make changes to specifications without prior notice. Bale/bag/bin weights are dependent upon material type.

## **ORWAK AB**

Svetsaregatan 4 S-576 33 Sävsjö SWEDEN Phone: +46-(0)382-15700 E-mail: info@orwak.com

# ORWAK COMPACT 3110 IS OPTIMIZED FOR:

### PAPER

- Cardboard
- Shredded paper

### P · P ·

OTHER METALS Steel straps

# PLASTIC FOIL

- Shrink film
- Plastic bags

#### OTHER PLASTICS Plastic straps

aps 📕


#### SILENT OPERATION CONTRIBUTES TO A BETTER WORKING ENVIRONMENT

Thanks to a silent type of hydraulics, the sound emission is low, which contributes to improving the working environment for the employees and is an important feature if the baler is installed close to customers.

# **ORWAK CONNECT COMMUNICATION**

The COMPACT balers are ready to communicate when choosing the option Orwak Connect. It is a modem-based communication service enabling the baler to send updates and alerts to the caretaker as well as vital information and bale statistics to the web portal.

Complies with the EN 16500:2014 safety requirement standard for vertical balers





# ORWAK.COM



Adjustable bale height in three sizes
Top cover made of recycled plastic

User-friendly panelAutostart

Bale trolley included

D

1460 mm