ORWAK POWER 3325

ORWAK POWER is a dynamic baler family based on an innovative hydraulic concept, Black Star Technology. Stronger, faster and smarter to give you more value for the money! The baler comes with a regular pendulum door. 3325 is a great choice for both cardboard and plastic and has especially good qualities for compaction of plastic foil.





Seconds

🛞 BLACK STAR TECHNOLOGY

DRWAK POWER

Orwak benefits

MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

MORE SPACE & ORDER

Our balers rapidly minimize the space the waste takes up, keeping aisles free and tidy.

LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO_2 emissions. Sorting at source yields a higher quality of waste material for recycling.





Why Orwak Power?

- + Powerful compaction of large volumes of waste
- Low-built design for easy transportation and rich placement opportunities
- + Intelligent features make you stay in control



POWER

Complies to EN 16500

Safety standard

ORWAK

BALE WEIGHT

www.orwak.com

ORWAK POWER 3325

ORWAK POWER 3325 IS OPTIMIZED FOR:

PAPER

- + Cardboard
- + Shredded paper

PLASTIC FOIL

- + Shrink film
- + Plastic bags

Great qualities for cardboard and particularly soft plastic

STRONGER

BLACK STAR TECHNOLOGY The innovative hydraulic concept, introduced by us as Black Star Technology, is based on the reverse technique of pulling instead of pushing the press-plate downwards when compacting material. Advantages:

- the cylinders are at its strongest point when pressure peaks
- a long piston stroke (1000 mm)

These factors contribute to powerful compaction into dense bales!

SOLID DESIGN ORWAK POWER, with its light spherical design, the ISO 3834-certified welding of the chamber and the durable cylinder design, is created for a long heavy-duty service life.

FASTER

Equipped with autostart!

RAPID BALER KEEPS UP WITH YOUR PACE

• More throughput at less energy consumption than in traditional baling systems!

Very short cycle time of only 24 seconds!



SMARTER

INTELLIGENT BALER

The new PCB features data storage capacity, technical machine monitoring, communication opportunities and - as forerunner in the baler business - fulfills performance level D for personal safety.

SPECIAL PLASTIC MODE


Equipped with a special software for successful compaction of plastic foil. It gets activated when the baler is run in the manual LP mode and will keep the waste under pressure for 5 minutes to squeeze out more air from the bulky plastic.

MORE GREAT FEATURES

- Low-built design for easy transportation and successful installation where space is limited
- Silent operation
- User-friendly panel & bale indicator
- Material selector HP (cardboard) & LP (plastic)
- Bales can be secured by polyester straps or wire
- Complies with the EN 16500:2014 safety requirement standard for vertical balers

DIMENSIONS & SPECIFICATIONS

DIMENSIONS									
Α	В	с	D	E	F*				
2380 mm	1775 mm	1060 mm	2325 mm	1153 mm	1980 mm**				



*Transport Height

1200 x

520 mm

**Transport feet add 100 mm but can be removed after unloading

TECHNICAL SPECIFICATIONS

LOADING APERTURE	CYCLE TIME	PRESS FORCE	BALE SIZE	BALE WEIGHT	NOISE LEVEL	MACHINE WEIGHT	OPERATING POWER				
Width: 1200mm Height: 520mm	24 secs	26 ton. 260 kN	Width: 1200mm Depth: 800mm Height: 1150mm	Cardboard: Up to 400 kg Plastic: Up to 450 kg	≤ 65 db (A)	1080 kg	3-phase 3x400 V, 50 Hz				

We reserve the right to make changes to specifications without prior notice. Bale weights are dependent upon material type.

Orwak AB Svetsaregatan 4 S-576 33 Sävsjö SWEDEN Tel: +46-(0)382-157 00 info@orwak.com, www.orwak.com

