


# BRICKMAN 2000K

BRICKMAN

**BRICKMAN 2000K IS OUR REAL HEAVY DUTY VERSION DEVELOPED TO MAKE THE TASK OF COMPACTING EXTRA LARGE QUANTITIES OF BULKY WASTE, SUCH AS CARDBOARD AND PET BOTTLES AS SIMPLE AS POSSIBLE.**

The automated solution is time-saving and convenient and Brickman 2000K has the capacity to process up to 25 000 empty PET-bottles per hour!



## Automatic solution



1500 K6/H

CAPACITY  
CARDBOARD

## Orwak benefits

### MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

### MORE SPACE & ORDER

Our balers rapidly minimizes the space the waste takes up, keeping aisles free and tidy.

### LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO<sub>2</sub> emissions. Sorting at source yields a higher quality of waste material for recycling.



## Why Brickman?

- + Convenient fully automated compaction solution
- + Impressive volume reduction of up to 20:1
- + Placement opportunities indoors



# BRICKMAN

## 2000K



### BRICKMAN 2000K IS OPTIMIZED FOR:

#### CARDBOARD

+ Corrugated cardboard

#### CAPACITY

up to 1500 kg/h

#### PLASTIC

+ PET bottles

#### CAPACITY

up to 1250 kg/h

### DESIGNED FOR HEAVY DUTY

Thanks to the following features, the robust briquette press Brickman 2000K is especially designed for compaction of large volumes of cardboard and empty PET bottles:

- + Extension on press cylinder
- + Automatic greasing of the press plate
- + Reinforced material in press chamber, press plate, cutting blades, guide piston and press loop

### OPTIONAL ACCESSORIES

Brickman 2000K can be ordered with a number of accessories; different chute options, start systems, sound absorption plates as well as heating and cooling devices. **NEW OPTION: Silent powerpack for very low sound emission.**

### CONVENIENT AND EFFICIENT

Brickman offers time-saving and comfortable waste handling. The press can be fed while running, there is no lid or door to open when loading the material and the ready briquettes require no binding. Furthermore, optional photocells can automatize the start function. The material infeed and briquette outfeed are easy to integrate in system solutions.

### GREAT LOGISTICS

Thanks to Brickman's compact dimensions, it can be placed indoors close to the waste disposal station.



## DIMENSIONS & SPECIFICATIONS

### DIMENSIONS (MM)

| A    | B    | C   | D    | E    | F    | G    | H    | I   | J    | K   | L    | M    | N   | O    | P   | Q    | R   |
|------|------|-----|------|------|------|------|------|-----|------|-----|------|------|-----|------|-----|------|-----|
| 2470 | 2010 | 905 | 1615 | 1420 | 1870 | 6300 | 1355 | 685 | 1600 | 920 | 1180 | 2430 | 265 | 1900 | 690 | 1350 | 535 |

### DIMENSIONS (MM)

| S   | T    | U    | V    |
|-----|------|------|------|
| 980 | 1960 | 1300 | 1660 |



### TECHNICAL SPECIFICATIONS

| MACHINE WEIGHT | PRESS FORCE    | PRESSURE                    | HOPPER           | BRIQUETTE SIZE     | DENSITY*                    | NOISE LEVEL | OPERATING POWER                                                                                          |
|----------------|----------------|-----------------------------|------------------|--------------------|-----------------------------|-------------|----------------------------------------------------------------------------------------------------------|
| 4000 kg        | 25 ton, 250 kN | Up to 62 kg/cm <sup>2</sup> | 2 m <sup>2</sup> | 200x200x100-300 mm | Up to 400 kg/m <sup>3</sup> | 80 db (A)   | 400 V, 3-phase, 50 Hz**<br>Fuse: 40 A (slow)<br>Engine: 18.5 kW<br>Voltage: 24 V<br>Protec. class: IP 55 |

We reserve the right to make changes to specifications without prior notice. \* Density varies with type of material. \*\* Other voltages are available