


BRICKMAN

300 LIQUID

BRICKMAN

THIS VERSION OF BRICKMAN 300 WITH EXTENDED CYLINDER IS DESIGNED FOR EFFECTIVE COMPACTION OF LARGE AMOUNTS OF PET BOTTLES AND ALUMINUM CANS CONTAINING LIQUID.

The automated solution is time-saving and convenient. Due to a small footprint and low sound emission, Brickman 300 can be placed indoors close to the source of waste.



Automatic solution



70 K6/H

CAPACITY
FILLED PET BOTTLES

Orwak benefits

MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

MORE SPACE & ORDER

Our balers rapidly minimizes the space the waste takes up, keeping aisles free and tidy.

LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO₂ emissions. Sorting at source yields a higher quality of waste material for recycling.



Why Brickman?

- + Convenient fully automated compaction solution
- + Impressive volume reduction of up to 20:1
- + Placement opportunities indoors



www.orwak.com

ORWAK[®]
PART OF **SULO** GROUP

BRICKMAN 300 LIQUID



BRICKMAN 300 LIQUID IS OPTIMIZED FOR:

FILLED CONTAINERS	CAPACITY
+ PET bottles	up to 170 kg/h
+ Aluminium cans	up to 160 kg/h

DESIGNED FOR CONTAINERS FILLED WITH LIQUID

Thanks to the following features, this sturdy version of Brickman 300 is especially designed for compaction of bottles and aluminum cans containing liquid:

- + Extension on press cylinder
- + Automatic greasing of the press plate
- + Reinforced material in press chamber, press plate, cutting blades, guide piston and press loop
- + Hopper, covers, shafts and briquette chute made of stainless steel
- + Galvanized machine stand and press plate

OPTIONAL ACCESSORIES

Brickman 300 Liquid can be ordered with a number of accessories; different chute options, start systems, sound absorption plates as well as heating and cooling devices.

CONVENIENT AND EFFICIENT

Brickman offers time-saving and comfortable waste handling. The press can be fed while running, there is no lid or door to open when loading the material and the ready briquettes require no binding. Furthermore, optional photocells can automatize the start function. The material infeed and briquette outfeed are easy to integrate in system solutions.

GREAT LOGISTICS

Thanks to Brickman's compact dimensions and low sound emission, it can be placed indoors close to the waste disposal station.



DIMENSIONS & SPECIFICATIONS

DIMENSIONS (MM)

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R
2270	1950	Ø145	425	1360	1500	1880	850	2190	660	3700	140	950	210	245	840	1440	600

DIMENSIONS (MM)

S	T
825	1100



TECHNICAL SPECIFICATIONS

MACHINE WEIGHT	PRESS FORCE	PRESSURE	HOPPER	BRIQUETTE SIZE	DENSITY*	NOISE LEVEL	OPERATING POWER
1600 kg	25 ton, 250 kN	Up to 500 kg/cm ²	0.75 m ²	80x80x100-300 mm	Up to 1000 kg/m ³	68 db (A)	400 V, 3-phase, 50 Hz** Fuse: 25 A (slow) Engine: 7.5 kW Voltage: 24 V Protec. class: IP 55

We reserve the right to make changes to specifications without prior notice. * Density varies with type of material. ** Other voltages are available

Orwak AB
Svetsaregatan 4
S-576 33 Sävsjö
SWEDEN
Tel: +46-(0)382-157 00
info@orwak.com, www.orwak.com

ORWAK
PART OF **SULO** GROUP